

QTY	PART NUMBER	PIPE SIZE	OAL
	400HT015012	1-1/2"	12"
	400HT015018	1-1/2"	18"
	400HT020012	2"	12"
	400HT020018	2"	18"
	400HT025012	2-1/2"	12"
	400HT025018	2-1/2"	18"
	400HT030012	3"	12"
	400HT030018	3"	18"
	400HT040012	4"	12"
	400HT040018	4"	18"
	400HT050012	5"	12"
	400HT050018	5"	18"
	400HT060012	6"	12"
	400HT060018	6"	18"
	400HT080012	8"	12"
	400HT080018	8"	18"
	400HT100012	10"	12"
	400HT100018	10"	18"
	400HT120012	12"	12"
	400HT120018	12"	18"
	400HT240012	24"	12"
	400HT240018	24"	18"

ALL JOINTS HAVE A MAXIMUM WORKING PRESSURE RATING OF 150 PSI @ 250°F

JOINTS ARE NOT RATED FOR COMPRESSION OR EXTENSION. FOR VIBRATION SERVICE ONLY. NOT INTENDED FOR TORSION.


THE FLEXIBLE JOINT SHOULD BE INSTALLED TO THE LENGTH SHOWN ON THE DRAWING. PIPING AND EQUIPMENT CONNECTED BY THIS FLEXIBLE JOINT MUST BE ANCHORED AND GUIDED.

PROJECT NOTES

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

REV.	DATE
	
2323 W. HUBBARD ST. CHICAGO, IL 60612 TEL: 312-738-3800 FAX: 312-738-0415 WWW.METRAFLEX.COM	
STYLE 400HT	
FLEXIBLE PIPE	
DRAWN BY: JULIANH	DATE: 01/07/2025
APPROVED: DKISH	DATE: 01/07/2025
SCALE: N/A	DRAWING NUMBER: 400HT-2